

Certificate of Analysis

Product name: CONDUCTIVITY STANDARD SOLUTION
1413 ± 5 µS/cm @ 25 °C (77 °F)
Product code: HI7031L
Lot number: 2208
Best use before: November 2022
Date of analysis: 2017.11.08
Certified value: 1411 µS/cm @ 25 °C (77 °F)

Method of standardization:

This quality product is standardized using a conductivity meter and probe periodically checked / calibrated against NIST primary standard solutions or primary standard solutions prepared following NIST guidelines (see NIST Special publication 260-142).

All primary standard solutions used are prepared from certified salts [as SRM 999] using deionized water for analytical use ISO 3696 / BS 3978.

Balances and thermometers used are checked with certified reference materials.

Uncertainty U:

The uncertainty interval represents the expanded uncertainty U with a coverage of 2 and represents the 95% level of confidence.

Reference number: 08K73
QA manager: Adela Odorhean



QC_HI7031x_rev.1

Certificate of Analysis

Product name: CONDUCTIVITY STANDARD SOLUTION
1413 ± 5 µS/cm @ 25 °C (77 °F)
Product code: HI7031L
Lot number: 2208
Best use before: November 2022
Date of analysis: 2017.11.08
Certified value: 1411 µS/cm @ 25 °C (77 °F)

Method of standardization:

This quality product is standardized using a conductivity meter and probe periodically checked / calibrated against NIST primary standard solutions or primary standard solutions prepared following NIST guidelines (see NIST Special publication 260-142).

All primary standard solutions used are prepared from certified salts [as SRM 999] using deionized water for analytical use ISO 3696 / BS 3978.

Balances and thermometers used are checked with certified reference materials.

Uncertainty U:

The uncertainty interval represents the expanded uncertainty U with a coverage of 2 and represents the 95% level of confidence.

Reference number: 08K73
QA manager: Adela Odorhean



QC_HI7031x_rev.1

Certificate of Analysis

Product name: CONDUCTIVITY STANDARD SOLUTION
1413 ± 5 µS/cm @ 25 °C (77 °F)
Product code: HI7031L
Lot number: 2208
Best use before: November 2022
Date of analysis: 2017.11.08
Certified value: 1411 µS/cm @ 25 °C (77 °F)

Method of standardization:

This quality product is standardized using a conductivity meter and probe periodically checked / calibrated against NIST primary standard solutions or primary standard solutions prepared following NIST guidelines (see NIST Special publication 260-142).

All primary standard solutions used are prepared from certified salts [as SRM 999] using deionized water for analytical use ISO 3696 / BS 3978.

Balances and thermometers used are checked with certified reference materials.

Uncertainty U:

The uncertainty interval represents the expanded uncertainty U with a coverage of 2 and represents the 95% level of confidence.

Reference number: 08K73
QA manager: Adela Odorhean



QC_HI7031x_rev.1

Certificate of Analysis

Product name: CONDUCTIVITY STANDARD SOLUTION
1413 ± 5 µS/cm @ 25 °C (77 °F)
Product code: HI7031L
Lot number: 2208
Best use before: November 2022
Date of analysis: 2017.11.08
Certified value: 1411 µS/cm @ 25 °C (77 °F)

Method of standardization:

This quality product is standardized using a conductivity meter and probe periodically checked / calibrated against NIST primary standard solutions or primary standard solutions prepared following NIST guidelines (see NIST Special publication 260-142).

All primary standard solutions used are prepared from certified salts [as SRM 999] using deionized water for analytical use ISO 3696 / BS 3978.

Balances and thermometers used are checked with certified reference materials.

Uncertainty U:

The uncertainty interval represents the expanded uncertainty U with a coverage of 2 and represents the 95% level of confidence.

Reference number: 08K73
QA manager: Adela Odorhean



QC_HI7031x_rev.1